



HYDRO TOP

WATERPROOF COATING

**ECOLOGIC | WATER-BASED | NON-FLAMMABLE
WITHOUT ORGANIC SOLVENTS**



FAD Christie & Co



Product manufactured in ISO 9001:2008
certified quality management system
and ISO 14001:2004 certified environmental
management system.



Description:
HYDRO TOP is a monocomponent flexible waterproofing membrane based on acrylic polymers in aqueous dispersion.

Application:
Before usage, the product must be homogenized in its original package. The surfaces on which the product will be applied must be dry and dust-free. Hydro Top can be applied using the airless spray gun, by brush or by roller. For absorbent surfaces, a primer can be made from Hydro Top by diluting it by 50% and applied before the paint. The waterproofing membrane is applied in two layers with an interval of 16-24 hours between layers. A glass fiber net or geotextile polyester fabrics (weight: 60-180 g/m²) can be applied between layers.

Application temperature: 10-35°C
The waterproofed surface must be protected from rain for 24 hours after application.
Tools must be cleaned with water immediately after usage.

Product consumption:
0.4 - 1.2 kg/m²/layer or 0.5-1.5 kg/m²

Security:
This product is not classified as dangerous. Keep out of reach of children. Avoid contact with skin and eyes. Don't dispose in sewage. Dispose the product and its package in safe places. In case of accident or sickness, reach out for medical assistance immediately. If possible, show the product label.

Mass: Sample

Storage temperature: 10-25°C.

Shelf-life: 36 months after fabrication date.

Colour: WHITE